



---

## Technical Sheet

# ANTIADESIVO 385

## (No-Adhesive 385)

The fluid **ANTIADESIVO 385** is a Polydimethylsiloxane liquid with odorless mineral spirit.

The **ANTIADESIVO 385** was developed for a production of rubber pipe by mandrel for high and low pressure of works, with different diameter and also for long meters

### TECHNICAL SPECIFICATIONS

Appearance	liquid
Color	transparent limpid
Specific weight at 20°C	0,90-0,95 gr/cm <sup>3</sup>
Flammability	90°C
Temperature of Distillation	from 90°C up to 190°C
Viscosity by Ford cup at 15°C	200-230 sec. ( with hole of diameter mm 2)

**Use:** Apply the product by brush or by other methods on the metal surface of the mandrel and starts the production of the rubber pipe.

It's also possible to pray the **ANTIADESIVO 385** on surface to lubricating.  
In case of product is too much viscosity, is possible to dilute with mineral spirit

The **ANTIADESIVO 385** also can be used as a lubricant or as antiadhesive for a mold or complex mold for rubber simple and complex article

### Packaging:

- Tank of 20 kg
- Bing tank of 1.000 lt (approx. 950 kg)

### ATTENTION:

Due a different kind of rubber, before starts with production, test ANTIADESIVO 385 with your rubber article